


RELIABILITY TEST PROCEDURES FOR ECS-2520SMV Series Oscillator



<u>NO.</u>	<u>TEST NAME</u>	<u>TEST PROCEDURES</u>	<u>REQUIREMENTS</u>
------------	------------------	------------------------	---------------------

1	SHOCK	Drop 3 times from the height of 100cm onto hard wooden board.	Frequency Drift ± 5 PPM Max. Resistance Drift $\pm 15\%$ Max.
2	VIBRATION	Vibration Frequency: 10 to 55Hz, 1.5mm, full wave Cycle: 2 min. Direction: X.Y.Z. Time: 2 hours in each direction	Frequency Drift ± 5 PPM Max. Resistance Drift $\pm 15\%$ Max.
3	STORAGE IN HIGH TEMPERATURE	$+85 \pm 2^{\circ}\text{C}$ for 500 hours.	Frequency Drift ± 5 PPM Max. Resistance Drift $\pm 15\%$ Max.
4	STORAGE IN LOW TEMPERATURE	$-40 \pm 2^{\circ}\text{C}$ for 500 hours.	Frequency Drift ± 5 PPM Max. Resistance Drift $\pm 15\%$ Max.
5	RESISTANCE TO SOLDERING HEAT	Pass through reflow for 10s (Max.) which is pre-heated at a temperature of $160^{\circ}\text{C} \pm 10^{\circ}\text{C}$ and $240^{\circ}\text{C} \pm 5^{\circ}\text{C}$	Frequency Drift ± 5 PPM Max. Resistance Drift $\pm 15\%$ Max.
6	HUMIDITY	$+ 60 \pm 2^{\circ}\text{C}$ in humidity 95% for 500 hours.	Frequency Drift ± 5 PPM Max. Resistance Drift $\pm 15\%$ Max.
7	THERMAL SHOCK	Supply 500 cycles as follows: Temperature shift shall be done within 30 sec. $-55 \pm 2^{\circ}\text{C}$ $+125 \pm 2^{\circ}\text{C}$ (30 min) <-----> (30 min)	Frequency Drift ± 5 PPM Max. Resistance Drift $\pm 15\%$ Max.
8	TEMPERATURE CYCLE	Supply 100 cycles as follows:  1 Cycle	Frequency Drift ± 5 PPM Max. Resistance Drift $\pm 15\%$ Max.
9	SEALING TIGHTNESS MIL-STD 202F METHOD 112D TEST C AND D	1) Dipping in Florinert at: $+125 \pm 5^{\circ}\text{C}$ for 5 min. (Gross Leak) 2) Leak rate shall be measured by using: Helium leak Detector (Fine Leak)	There are no visual abnormalities. There are no visual abnormalities.
10	Mean Time Between Failures (MTBF)	$\text{MTBF (25}^{\circ}\text{C)} = \frac{E_a \times (1/T_1 - 1/T_2) / K}{\pi}$	16396600 Hours